



TECHNICAL DATA SHEET

WHITENING PASTE "DRIFTWOOD"

0696 - 0698

These whitening pastes modify completely the appearance of the aging agents, giving them a washed-out look.

- The paste **0696** is used for oak and tannic wood, for spruce and resinous wood.
- The paste **0698** is used for spruce and resinous wood, for oak and tannic wood.

PREPARATION

Mix the powder with water so as to obtain a smooth paste, the amount of powder which should be added depends of the application method chosen.

- 100 - 200 g for pulverization
- 150 - 300 g and more for an application with a brush.

APPLICATION

- The paste should be applied either by pulverization (field sprayer), with a machine or a paint brush in a fine or thicker coat (before pulverizing, the mixture should be filtered)
- Following the drying period, any surplus should be eliminated with a brush or with a damp sponge or a green pad, by hand or with a machine.

FINISH

The wood prepared in this way may be given different finishes (see sheets 0842 0844 – 0852 0853): a wax 0244 a parquet oil 0218, a chalet oil wax 0273 interior and exterior 0271 matt anti uv.

The whitening paste may be colored by adding pigments; in order to whiten it titan oxide should be added, to color it ochre yellow, ochre red, or ultramarine blue should be added.

SECURITY

- ⚠ Please read the security instructions carefully
- ⚠ Work in a well ventilated room
- ⚠ Wear rubber gloves
- ⚠ Do not swallow
- ⚠ Keep it away from the access of children

Information and details are given here in good faith but without involving our responsibility.

LES BONS PRODUITS St ANTOINE - ANCIENNE PROVENCE - EUROWOOD LASURE

21, rue André Chénier 69120 Vaulx en Velin (Grand Lyon) - France

Tel. 33 (0) 4 72 35 16 27 - Fax. 33 (0) 4 78 54 53 71 - E-Mail: easylab@easylabfinish.com

Internet: www.easylabfinish.com - RCS LYON B 39 783 712 00046 - NAF: 245 C