

EASY LAB



TECHNICAL DATASHEET

RUST PROTECTOR 0861

STOPS AND PROTECTS OUTSIDE / INSIDE - COLOURLESS / SATIN OR MATT

This protective coating for iron-rusted or not- contains corrosion inhibitor - and guarantees the new metal from further rust process. Moreover, it does not change the colour of rust, protects and patina. Protective-film is flexible (to ensure sustainability in the sun).

APPLICATION

Should not be applied on a hot metal or in the sun.





It is applied by brush or spray in 4 even layers on a metal which is dry and free from grease. The dust of the rust should be eliminated with a fine wire brush.

Drying between each layer 6-8 hours at 20 °C. Maximum hardness is obtained after 48 hours. Should the bleaching of the RUST PROTECTOR occur, as a result of a residue of moisture on the metal, a thinner 0402 should be applied in a fine coat. A decor may be made by created by using the RUST PROTECTOR PASTEL 0862 in various different colours.

QUANTITIES

15-18 m²/litre

SECURITY

-  Please read the security instructions carefully
-  work in a well aired room
-  wear rubber gloves
-  keep out of reach of children.

This information is given here in good faith but does not involve our responsibility.

LES BONS PRODUITS St ANTOINE - ANCIENNE PROVENCE - EUROWOOD LASURE

21 rue André Chénier 69120 Vaulx en Velin - France

Tel. 33 (0)4 72 35 16 27 - Fax. 33 (0)4 78 54 53 71 - E-Mail : easylab@easylabfinish.com

Internet : www.easylabfinish.com - RCS LYON B 349 783 712 00046 - NAF : 245 C