



TECHNICAL DATASHEET

Wood Aging by Oxidation Instructions for use with woods high in tannins

Always test products prior to commencing projects.

Greying & Aging by Oxidation (Grey, Pale Grey, Cognac, Tobacco)

For woods high in tannins – Oaks, Walnut, etc.

Basic combinations:

Pale Grey #1 0842 + Let Dry + 0844 + Let Dry + H²O

Pale Grey #2 0852 + Let Dry + 0844 + Let Dry + H²O

Grey Driftwood 0842 + Let Dry + 0844 + Let Dry + 0698(100g/L) + Let Dry + PAD

Tobacco 0843

Pale Tobacco 0843 + Let Dry + 0844

Cognac 0842 + Let Dry + 0843

Pale Cognac 0842 + Let Dry + 0843 + Let Dry + 0844

Whisky 0842 + Let Dry + 0696(100g/L) + Let Dry + 0844 + PAD

****Let dry 24 hours before applying finishes.***

Instructions:

0842, 0843, 0844 (LIQUIDS) – Products are ready to use; do not dilute.

When storing products be sure to keep away from direct sunlight and areas of high heat. Store inside.

Do not store in metal containers. Liquids will cover approximately 400 sqft per gallon depending on wood and application.

1. Prep wood (sanding, brushing, etc.)
2. Apply by spray or foam brush
3. Let thoroughly dry for 1 to 3 hours at room temperature before applying the next product. Do not let dry in direct sunlight.
4. There is no need to sand prior to sealing.

Notes: **Do not shake 0842 prior to use.**

0696/0698 (POWDER) – Mix 100 grams of 0696/0698 to 1 liter of water. Shake well. Allow to rest for 10 minutes. Then shake well again prior and during use. Covers approximately 450 sqft per liter at 100 grams per liter of water depending on wood and application.



TECHNICAL DATASHEET

1. Prep wood (sanding, brushing, etc.)
2. Apply by spray or foam brush
3. Let dry thoroughly. This product may be left to dry in direct sunlight.
4. After drying thoroughly, lightly scrub with a scouring pad such as a green Scotch Brite pad.
5. Remove dust with a brush or towel.
6. **Shake well before and during use.**

****Always test products prior to commencing projects.****

Greying & Aging by Oxidation

For woods low in tannins – Pine, Spruce, Fir, Poplar, etc.

0853 & 0852 (LIQUIDS) – Products are ready to use; do not dilute.

Use the 0853 first then use the 0852

Basic combinations:

0853 + 0852 + 0698

0853 + 0852 + 0843 + 0698

Instructions:

When storing products be sure to keep away from direct sunlight and areas of high heat. Store inside.

Do not store in metal containers. Liquids will cover approximately 400 sqft per gallon depending on wood and application.

1. Prep wood (sanding, brushing, etc.)
2. Apply by spray or foam brush
3. Let thoroughly dry for 1 to 3 hours at room temperature before applying the next product. Do not let dry in direct sunlight.
4. There is no need to sand prior to sealing.

FINISHES

0218 Tall Oil Finish Clear – Protection for Hardwood Floors. Water Based Tall Oil. Ready to use. For Hardwood Floors, Furniture and Woodwork. This oil emulsion is non-yellowing and leaves the wood with a beautiful natural look.



TECHNICAL DATASHEET

1. Make sure surface is clean and dust free
 2. Apply evenly with a brush or roller
 3. To achieve more of a sheen you may buff gently with a soft "white pad"
 4. Do NOT apply by "rubbing" into the wood
 5. Apply a second coat if desired within 30 minutes to an hour.
 6. Do not apply in direct sunlight or on excessively warm or hot surfaces.
 7. DO NOT use cleaners or chemicals to clean floors treated with 0218 Finishing Oil.
- DO NOT use Natural Oil Floor cleaners. (0218 Finishing Oil is a water-based Tall emulsion).
- 8. Shake well before use**

0244 Finishing Wax - Clear, Self-Shining Emulsion. Water Based. Ready to use. For Hardwood Floors, Furniture and Woodwork. This Carnuba based finishing wax gives the wood a beautiful luster and sheen. May be used in conjunction with the 0218 Finishing Oil for maximum protection.

1. Make sure surface is clean and dust free
 2. Apply using a brush, sprayer or paint roller, in 1 or 2 thin, even coats. After drying, polish with a soft polishing brush or cloth.
 3. Do not apply in direct sunlight
 4. Do not apply on excessively warm or hot surfaces
- 5. Shake well before use**

****Always test products prior to commencing projects.****

MAINTENANCE

*Maintenance for **0218 Finishing Oil:***

Use:

0214 Easy Maintenance - For floors treated with 0218 Finishing Oil.

1. Sweep the surface well.
2. Apply with a sponge or sponge mop, wringing out excess.
3. Sponge or mop should be damp, not wet.

Do not apply in direct sunlight or on excessively warm or hot surfaces.

DO NOT use cleaners or chemicals to clean floors treated with 0218 Finishing Oil. **DO NOT** use Natural Oil Floor cleaners. (0218 Finishing Oil is a water-based Tall emulsion)

Use for Hardwood Floors, Furniture and Woodwork Treated with 0218 Finishing Oil.



TECHNICAL DATASHEET

Maintenance for **0244 Finishing Wax:**

1. Dust mop or vacuum regularly. DO NOT use chemicals or cleaners.
2. Use a buffer with a "SOFT" polishing brush to maintain the shine.
3. Reapply 0244 Finishing Wax as needed. Apply using a "T-Bar" with a Lambswool Floor Coater refill as this will assure a thin even coat.

DO NOT pour the 0244 Finishing Wax directly onto the floor as this will cause staining. Pour wax into a bucket, dip the applicator into the wax, remove excess, and then apply evenly. You may dilute the 0244 Finishing Wax with water up to 10% to minimize "overlap" marks. (Always test the application method in a small unseen area to make sure you achieve the desired results).

Easy Lab USA, LLC, PO Box 262, Monrovia, CA 91017, (626) 239-8180

easylabusa@easylabusa.com